



東庚實業股份有限公司  
TONG GENG ENTERPRISE CO., LTD.

13F-5,NO. 6.SEC. 2,DAH HSING WEST ROAD,TAO YUAN CITY,TAIWAN

TEL:886-3-301 6886,FAX:886-3-301 6568,E-mail:yangty@tpts5.seed.net.tw

**ROR-2-400**

**Rapid High Temp. & Pressure Fabric Dyeing Machine**

<b>Main Information</b>	
<b>Max. Temperature</b>	140 °C
<b>Max. Pressure</b>	4 Kg/Cm2(bar)
<b>Main Stainless Steel</b>	SUS # 316/316 L(Japan/Europe)
<b>Loading Capacity</b>	Max. 200 Kgs/Tube
<b>Lowest Liquor Ratio</b>	Min. 1:4-5(1:5-6 for Cotton)
<b>Running Speed</b>	Max. 600 M/min.
<b>Total Power</b>	13 Kw
<b>Dyeing Kier</b>	
<b>Main Pump &amp; Motor</b>	10 HP
<b>No. Inside Store design</b>	Stainless steel BodyX 2 Pcs
<b>No. Operation Door</b>	2 Pcs
<b>Full Flow Pipe</b>	2 Pcs
<b>Patent Plaiting Device</b>	1 Pc
<b>Nozzle Size Changable</b>	φ 3.5''X2 Pcs+ φ 4.5''X2 Pcs
<b>Nozzle Pressure Adjust Valve</b>	1 Pc
<b>Nozzle Pressure Gauge</b>	0-10 Kg/cm2(bar)X1 Pc
<b>Main Reel &amp; Motor+Inverter</b>	2 HPX1 Pcs
<b>No. Water Inlet</b>	1+1 Pcs
<b>No. Water Outlet</b>	1+1 Pcs
<b>No. Overflow Outlet</b>	1 Pc
<b>Auto Level indicator</b>	1 Set
<b>Auto Pressure air Inlet &amp; Out</b>	1 Set
<b>Safety Valve</b>	1 Set
<b>No. Filter Cabin</b>	1+1(Spare)
<b>Thermometer</b>	1 Pc(0-150 °C)
<b>Kier inside Pressure Gauge</b>	0-10 Kg/cm2(bar)X1 Pc
<b>Unloading Reel with Reducer</b>	1 HPX1 Pc
<b>Power Drain Outlet</b>	1 Pc